





BEVERAGE SPECS REFRESHER SPECS

REFRESHER SPECS

[VIEW ALL SPECS \[+ \]](#)

Body & Chassis [-]

Frame	Welded steel with DuraShield™ powder coating
Front Body & Finish	Molded-in color Gelyo XTW
Rear Body & Finish	Steel, base coat/clear coat
Standard Color	Forest Green

Dimensions [-]

Overall Length	110.5 in (280 cm)
Overall Width	49.8 in (126 cm)
Overall Height (no canopy)	48.6 in (123 cm) (top of steering wheel)
Overall Height (with canopy)	72.0 in (183 cm)
Wheel Base	77.0 in (196 cm)
Front Wheel Track	37.0 in (94 cm)
Rear Wheel Track	38.0 in (97 cm)
Ground Clearance (at differential)	3.3 in (11 cm)

Power [-]

Power Source	4 cycle, 24.5 ci (401 cc) low emissions
Valve Train	Single cylinder OHV
Horsepower (kW)	13 hp (9.7 kW) SAE J1940 Standard
Electric System	Starter/generator, solid state regulator
Battery (qty/type)	One 12-volt maintenance-free
Air Cleaner	Cyclonic, industrial-rated dry filter
Lubrication	Pressurized oil system
Oil Filter	Spin-on
Cooling System	Air cooled
Fuel Capacity	6.0 gallons (22.8 L)
Drive Train	Automatic, continuously variable transmission (CVT)
Transaxle	Differential with helical gears
Gear Selection	Forward-Reverse
Rear Axle Ratio	11.42:1 (Forward) 15.78:1 (Reverse)

Performance [-]

Seating Capacity	2-person
Dry Weight	1365 lb (620 kg)
Curb Weight	1405 lb (638 kg)
Vehicle Load Capacity	1200 lb (545 kg)
Outside Clearance Circle	22 ft (6.7 m)
Ground Speed Forward	11.0 mph ± 0.5 mph (17.7 kph ± 0.8 kph)
Ground Speed Reverse	8.0 mph ± 0.5 mph (12.9 kph ± 0.8 kph)

Steering & Suspension [-]

COLOR OPTIONS 360° ENLARGE

[WHERE TO BUY](#)

[CUSTOMIZE MY E-Z-GO](#)

[STANDARD FEATURES](#)

[OPTIONS/ACCESSORIES](#)

[OTHER MODELS](#) ▼

Rear Suspension	Leaf springs with hydraulic shock absorbers
Service Brake	Rear wheel mechanical self-adjusting drum
Parking Brake	Self-compensating single-point engagement
Front Tires	Links 18 x 8.50-8 (4-ply rated)
Rear Tires	Turf Saver 18 x 8.50-8 (load range B)