





ST 400

EQUIPPED TO HAUL

With an 800 lb total capacity, powerful 13 hp Kawasaki® engine, CVT automatic transmission and roto-molded heavy-duty cargo bed, the ST 400 is ready to tackle your biggest jobs. Twenty-two inch Stryker tires and optional front-mounted winch provide surefooted traction and pulling power.

COLOR OPTIONS 360° ENLARGE

WHERE TO BUY

CUSTOMIZE MY E-Z-GO

STANDARD FEATURES

OPTIONS/ACCESSORIES

OTHER MODELS

GAS SPECS

VIEW ALL SPECS [+]

Body & Chassis [-]

Frame	Welded tubular steel with DuraShield™ powder coating
Front Body & Finish	Injection-molded Gelyo XTW
Rear Body & Finish	Steel, base coat/clear coat
Standard Color	Forest Green

Dimensions [-]

Overall Length	111.5 in (283 cm)
Overall Width	50.0 in (127 cm)
Overall Height (no canopy)	49.0 in (125 cm) (top of steering wheel)
Overall Height (with canopy)	73.0 in (185 cm)
Wheel Base	77.0 in (196 cm)
Front Wheel Track	38.0 in (96 cm)
Rear Wheel Track	38.5 in (97 cm)
Ground Clearance (at differential)	6.0 in (15 cm)
Cargo Box Width (inside)	44.0 in (112 cm)
Cargo Box Length (inside)	36.0 in (91 cm)
Cargo Box Depth (inside)	10.5 in (27 cm)
Cargo Box Capacity	9.6 cu ft (0.27 m ³)
Cargo Box Material	Roto-molded polyethylene

Power [-]

Power Source	4 cycle, 24.5 cu in (401 cc) low emission
Valve Train	Single cylinder OHV
Horsepower (kW)	13 hp (9.7 kW)
Electric System	Starter/generator, solid state regulator
Batteries (qty, type)	One 12-volt, maintenance-free
Air Cleaner	Dry cartridge with remote intake
Lubrication	Pressurized oil system
Oil Filter	Spin on
Cooling System	Air-cooled
Fuel Capacity	6 gallon (22.8 L)
Drive Train	Automatic, continuously variable transmission (CVT)
Transaxle	Differential with helical gears
Gear Selection	Forward-reverse
Rear Axle Ratio	13:32:1

Performance [-]

Seating Capacity	2-person
Dry Weight	900 lb (410 kg)
Curb Weight	940 lb (430 kg)
Bed Load Capacity	500 lb (225 kg)
Vehicle Load Capacity	800 lb (360 kg)

Circle	
Forward Ground Speed	17 mph \pm 0.5 mph (27.4 kph \pm 0.8 kph)
Reverse Ground Speed	12.3 mph (19.8 kph)
Towing Capacity	500 lb (225 kg)
Steering & Suspension [-]	
Steering	Self-compensating rack and pinion
Front Suspension	Leaf springs with hydraulic shock absorbers
Rear Suspension	Leaf springs with hydraulic shock absorbers
Service Brake	Rear wheel mechanical self-adjusting drum brakes
Parking Brake	Self-compensating, single point engagement
Front Tires	Stryker 23 x 9-10 uni-directional
Rear Tires	Stryker 23 x 9-10 uni-directional